

Service Crimper Comparison



KC1-H47E



KC1-H47PM



KC1-H47PI

Crimping Force (ton)	110	110	110
Max. Capacity 1-2 Wire Braided (in)	1	1	1
Max. Capacity 4 Spiral (in)	NA	NA	NA
Max. Capacity 6 Spiral (in)	NA	NA	NA
Max. Capacity Industrial (in)	NA	NA	NA
Power	Hand, Air or Battery	Hand	Air
Max. Opening with Dies (mm / in)	49 / 1.93	49 / 1.93	49 / 1.93
Page Number	5	6	7



KC1-H64PM



KD165



KC2-J67

Crimping Force (ton)	132	62	190
Max. Capacity 1-2 Wire Braided (in)	1 1/2	1 1/4	1 1/2
Max. Capacity 4 Spiral (in)	1 1/4*	1 1/4**	1 1/4*
Max. Capacity 6 Spiral (in)	NA	NA	NA
Max. Capacity Industrial (in)	NA	NA	NA
Power	Hand	1 HP (110 V)	1.5 HP (110 V)
Max. Opening with Dies (mm / in)	69 / 2.72	NA	NA
Page Number	8	9	10

* 1 1/4" up to 4,000 PSI, 1" up to 5,000 PSI

** 1 1/4" up to 3,000 PSI, 1" up to 4,000 PSI

Because we continually examine ways to improve our products, we reserve the right to alter specifications or discontinue products without prior notice.