



**KC1-H83                      KC3-H88                      KC1-H130                      KC3-H130**

<b>Crimping Force (ton)</b>	150	150	210	210
<b>Max. Capacity 1-2 Wire Braided (in)</b>	1 1/2	1 1/2	2	2
<b>Max. Capacity 4 Spiral (in)</b>	1 1/4	1 1/4	2	2
<b>Max. Capacity 6 Spiral (in)</b>	1	1	1 1/4	1 1/2*
<b>Max. Capacity Industrial (in)</b>	1 1/2	1 1/2	3	3
<b>Max. Opening without Dies (mm / in)</b>	111 / 4.37	111 / 4.37	154 / 6.06	154 / 6.06
<b>Max. Opening with Dies (mm / in)</b>	96 / 3.78	102 / 4.02	108 / 4.25	108 / 4.25
<b>Power</b>	4.0 HP (230 V)	4.0 HP (230 V)	2.9 HP (230 V)	2.9 HP (230 V)
<b>Page Number</b>	12	13	14	15

\* Limited to intermittent use with 5,000 PSI Alfagomma hose using 1-pc fittings



**KC1-H135                      KC3-H135                      KC3-H144                      KC3-H170**

<b>Crimping Force (ton)</b>	330	330	440	308
<b>Max. Capacity 1-2 Wire Braided (in)</b>	2	2	2 1/2	2
<b>Max. Capacity 4 Spiral (in)</b>	2	2	2 1/2	2
<b>Max. Capacity 6 Spiral (in)</b>	2	2	2	2*
<b>Max. Capacity Industrial (in)</b>	3	3	4	4†
<b>Max. Opening without Dies (mm / in)</b>	162 / 6.38	162 / 6.38	203 / 7.99	219 / 8.62
<b>Max. Opening with Dies (mm / in)</b>	139 / 5.47	139 / 5.47	176 / 6.93	192 / 7.56
<b>Power</b>	7.5 HP** (230 V)	7.5 HP (230 V)	7.5 HP (230 V)	7 HP (230 V)
<b>Page Number</b>	16	17	18	19

\* Limited to 5,000 PSI Alfagomma hose using 1-pc fittings

\*\* 5.5 HP for single phase

† Up to 5" depending on hose and coupling type

Because we continually examine ways to improve our products, we reserve the right to alter specifications or discontinue products without prior notice.